

Supporting Information for Publication

From LUVs to GUVs - How to Cover Micrometer-Sized Pores with Membranes

Kristina Kramer,[†] Merve Sari,[†] Kathrin Schulze,[†] Hendrik Flegel,[†] Miriam Stehr,[†]
Ingo Mey,[†] Andreas Janshoff,[‡] and Claudia Steinem^{*,†,¶}

[†]*Institute of Organic and Biomolecular Chemistry, University of Göttingen,
Tammannstrasse 2, 37077 Göttingen, Germany*

[‡]*Institute of Physical Chemistry, University of Göttingen, Tammannstrasse 6, 37077
Göttingen, Germany*

[¶]*Max Planck Institute for Dynamics and Self-Organization, Am Fassberg 17, 37077
Göttingen, Germany*

E-mail: csteine@gwdg.de

Phone: +49 551 39 23294




Figure S1: Indirect FRAP experiment and FEM simulations for the determination of the lipid diffusion coefficient of the s-PSM. (A) Exemplary fluorescence micrographs of an indirect FRAP experiment. Fluorescence intensity was bleached in a ROI ($r_n = 2.2\text{-}2.3 \mu\text{m}$) on top of an entire f-PSM and the fluorescence recovery was observed over time. Scale bar: $5 \mu\text{m}$. Normalized, averaged fluorescence recovery curves of indirect FRAP experiments of the s-PSM on (C) Au/6MH and $\text{SiO}_{1 \leq x \leq 2}$ coated substrates. Simulated recovery curves were modeled for $D_{\text{f-PSM, sim}} = 13 \mu\text{m}^2 \text{s}^{-1}$ and different $D_{\text{s-PSM, sim}} = 0.5\text{-}3 \mu\text{m}^2 \text{s}^{-1}$. Lipid diffusion coefficients of the s-PSM on Au/6MH functionalized substrates of $D_{\text{s-PSM, Au}} = 2 \mu\text{m}^2 \text{s}^{-1}$ and on $\text{SiO}_{1 \leq x \leq 2}$ coated substrates $D_{\text{s-PSM, SiO}} = 1.5 \mu\text{m}^2 \text{s}^{-1}$ agreed best with the experimental data.




Figure S2: (A) Atomic force micrographs of PSMs prepared by spreading electroformed GUVs on porous substrates ($d_{\text{pore}} = 1.2 \mu\text{m}$) functionalized with Au/6MH or SiO_{1≤x≤2}. Scale bars: 5 μm . (B) Atomic force micrographs and corresponding height profiles along the black solid line.




Figure S3: (A) Exemplary force-displacement curve measured in the center of an f-PSM. Influence of (B) indentation speed and (C) loading force on the lateral membrane tension. Force-displacement curves were obtained from PSMs derived from microfluidic GUVs on SiO_{1≤x≤2} functionalized substrates (B) at different indentation speeds ($n_{\text{all}} = 62$) and (C) loading forces ($n_{0.2} = 85$, $n_{0.4} = 62$, $n_{0.8} = 30$, $n_{1.2} = 32$). Statistical t-test: $p > 0.05$ (ns).




Figure S4: Parametrization of a pore-spanning membrane that is indented with a conical indenter. The symmetry is centrosymmetric. The pore edges (dark blue) act as a hinge to fix the biased membrane (green), which forms a catenoid to minimize the area or free energy. a denotes the contact radius of the membrane with the indenter, while z is the total depth of indentation. θ is the contact angle with the indenter, while $90 - \theta$ is half the angle of the cone.